

innovative LIGHTS



RHEA-B

RHEA-B, diese Serie hat 2 verschiedene IP-Werte zur Auswahl .
IP44 eignet sich für den Einsatz in feuchten Umgebungen. IP65 hat eine bessere Wasserbeständigkeit, kann in feuchter Umgebung verwendet werden. RHEA-B sind in geraden und verstellbaren Modulen erhältlich. Durch die Verwendung derselben Einbaugehäuse können Sie die Leuchte schnell umbauen. Das Modul und die Verkleidung sind mit Clips befestigt, was die Wartung komfortabler macht.



Lieferbare Farben - A / B

● Black ○ White




Article number	1718.141
LED Consumption	25.9W
Current	700 (mA)
Lumen	2559 (lm)
Beam Angle	12°/24°/40°
CCT	3000K
CRI	90+

Colours  
Black White



Dimmable





Article number	1718.142
LED Consumption	25.9W
Current	700 (mA)
Lumen	2559 (lm)
Beam Angle	12°/24°/40°
CCT	3000K
CRI	90+

Colours  
Black White



Dimmable






Article number	1618.169
LED Consumption	25.9W
Current	700 (mA)
Lumen	2559 (lm)
Beam Angle	12°/24°/40°
CCT	3000K
CRI	90+

Colours Black White



Dimmable



Article number	1618.170
LED Consumption	25.9W
Current	700 (mA)
Lumen	2559 (lm)
Beam Angle	12°/24°/40°
CCT	3000K
CRI	90+

Colours Black White



Dimmable

